TORO Count on it.

MH-400

FEATURES

Accurate – *Intuitive settings and operating system deliver a perfect spread every time. Repeatable settings for consistent performance and defined edges.*

Wireless Remote Operation – *Available wireless controller allows real-time adjustments. Make quick setting changes and store settings for future use. Base model features a wired controller.*

Spread Consistency – *Ultra Light to Ultra Heavy - Evenly apply materials from 9' (2.74 m) narrow to 35' (10.67 m) wide with the use of our unique "drop zone" patented sliding adjustment.*

Dependable – *All-steel construction, heavy duty components and low maintenance provide long life and reliable performance.*

Versatile – *The twin spinner accessory can be swapped out with a 270 degree swivel cross-conveyor quickly and easily without tools. Elevate the rear to a height of 6' (2m) and fill the ProPass topdresser with material, or use as a multi-purpose dump trailer. Optional brakes available.*

The Original Material Handler. And Then Some.

The large capacity MH-400 delivers versatility and performance to tackle a wide range of jobs at any facility. The cross conveyor is ideal for completing bunker and greens renovations, cart path rebuilding, applying mulch, back filling of drainage ditches, and much more. Install the twin spinner accessory and the MH-400 becomes a large area topdresser to transport and accurately spread materials ranging from crumb rubber, to fertilizer, to a sand/peat topdressing mix. The rear hitch receiver allows implements, such as a wood chipper, to be towed in tandem.

An integral component of any maintenance program, the efficient MH-400 reduces labor, saves time and cuts operating costs.

Chassis features a 4-wheel walking beam suspension for a light footprint on sensitive turf

Twin spinner option

Call your Toro distributor at 1-800-803-8676

MH-400 Specifications

	MH-400, MODELS 44930 & 44931 / MH-400 WIRELESS, MODELS 44933 & 44934*
GENERAL	Hopper Capacity: 4 yd3 (3.06 m3) Main Conveyor Belt: One Piece Vulcanized, Self Tracking, 30" wide Controls: Standard Hydraulic (SH) or Electronic Hydraulic (EH)
WEIGHT	Base Model: 3,000 lbs (1,360 kg) - empty with no options installed
CHASSIS	Payload (tare): 11,800 lbs (5,353 kg) GVWR: 14,800 lbs (6,713 kg) Suspension: 4 Wheel Walking Beam with 10 ply turf tires Tire Size: 33 x 16 x 16.1 in (82.5 x 40 x 40.25 cm) 10 ply Brakes (electric) - Optional 2 or 4 wheel
DIMENSIONS	Length 190 in (4.8 m) Height 86 in (2.2 m) Width 78 in (1.98 m)
TOW VEHICLE REQUIREMENTS	Towing Capacity: 15,850 lbs (7,175 kg) - maximum payload Minimum Power: 45 Hp (34 Kw)
HYDRAULICS	Recommended Flow (min no options installed): 6 US gal/min (23 L/min) Recommended Flow (min options installed): 10 US gal/min (38 l.min) Recommended Input Pressure (min): 2,000 psi (138 bar)
WARRANTY	Two-year limited warranty. Refer to operators manual for further details.
CE REQUIREMENTS	Meets the CE requirements for the EU

©2010 The Toro Company
8111 Lyndale Ave. S.
Bloomington, MN 55420-1196
Printed in the U.S.A.
Part No. 10-081-T

*Specifications subject to change. Please contact your Toro distributor for details.